Residential Commercial Off Grid Applications Solar Charge Controllers

Basic Information

Our Product Introduction

φ

more products please visit us on fuhaosolar.com

• Place of Origin: . Brand Name: СХ Model Number: CXLT • Minimum Order Quantity: 50 pieces

• Price: consult prices online Packaging Details: consult online Payment Terms: T/T



Product Specification

12V/24V Auto Or 12V/24V/48V Optional • Rated Voltage: • Rated Charge Current: 10A/20A, 30A/40A, 50A, Or 60A

• USB Output:

• Product Size: Varies By Model (e.g., 136×95×33mm To

190×110×50mm)

• Weight Per Carton: Varies By Model (e.g., 13kg To 17kg)

• Volume Per Carton: 0.03CBM To 0.05CBM • Highlight:

Residential solar power charge controller,

Commercial solar power charge controller, Off Grid solar system charge controller



More Images











LT-40-3

Product Description

Solar Charge Controllers for Residential Commercial and Off-Grid Applications

Product Description:

This solar charge controller is designed to efficiently manage the charging and discharging processes in solar power systems. It is equipped with features like over-voltage protection, short-circuit protection, low-voltage protection, and temperature compensation, ensuring reliable performance under various environmental conditions. With an intuitive LCD display, it provides real-time data monitoring, allowing for easy adjustment of parameters. The controller is versatile, supporting 12V/24V/48V configurations, and is compatible with both lithium-ion and lead-acid batteries. Its modular design makes it suitable for different solar installations, from residential to commercial applications.

Rated Voltage Rated Charge Current USB Output ProductSize Set/Carton Weight/Carton Measurement Volume/Carton							
12V/24VAuto	10A/20A	2A/5V	136×95×33m m	50Pcs	13Kg	470×320×220 mm	0.03CBM

Rated Voltage Rated Charge Current USB Output Product Sie Set/Carton Welght/Carton Measurement								
Volume/Carton	-							
12V/24V48V	30A/40A	2A/5V	162*96×38m	40Pcs	14Ka	475×375×230	0.04CBM	
Optiona	DUA 40A	EA/3V	m	701 03	i T iNg	mm	P.OTOBIVI	

		Ouput	Product Stze Set/Carton Weilght/Carton Measurement Volume/Carton					
12V/24V/48V Optiona	50A	2A/5V	176×103×38 mm	40Pcs	15.3Kg	570×400×205 mm	0.04CBM	

Rated Voltage Rate Volume/Carton	ed ChargeCurr	ent USB Ou	utput Product S	SizeSet/0	Carton We	ight/Carton Mei	surement
12V/24V48V Optional	60A	2A/5V	190×110×50 mm	30Pcs	17Kg	440×380×300 mm	0.05CBM

Application:

This solar charge controller is perfect for residential, commercial, and off-grid solar power systems. It ensures the longevity and safety of batteries while maintaining efficient energy storage and distribution. Ideal for homes, RVs, and small commercial establishments that require reliable solar energy management.

Shipping Methods

Supports global air and sea shipping.



RICHGOOD ENERGY CO.,LTD





willa@fuhaosolar.com fuhaosolar.com

Rm3810 Baoli E Building Pa Zhou Haizhu district Guangzhou