



# Remote Monitoring And Control E-SUN Hybrid Inverters With Wi-Fi And GPRS

## **Basic Information**

Place of Origin: China
Brand Name: TP
Certification: CE
Model Number: ESUN4t6
Minimum Order Quantity: 10 units

Price: consult prices onlinePackaging Details: consult online

Payment Terms: T/T



## **Product Specification**

• Rated Output Power: 7000VA For The E-SUN 4.2KVA And

11000VA For The E-SUN 6.2KVA

• PV Input Voltage Range: 40V To 450VDC (supports High Voltage

Solar Arrays)

Battery Voltage: 24VDC For E-SUN 4.2KVA, 48VDC For E-

SUN 6.2KVA

Current: Conversion

• Surge Power: 7000VA (E-SUN 4.2KVA), 11000VA (E-SUN


6.2KVA)

• Efficiency (Peak): 93.5% (E-SUN 4.2KVA) And 94% (E-SUN

6.2KVA)

• Highlight: 40V Hybrid Inverters, E-SUN Hybrid Inverters,

24V inverter off grid hybrid



## **Product Description**

#### Remote Monitoring and Control E-SUN Hybrid Inverters with Wi-Fi and GPRS

#### MAIN FEATURES

Pure sine wave solar inverter(on/off Grid)



WiFi&GPRS available for IOS and Andriod



Inverter can run without battery



High PV input voltage range (40~500VDC)



Dual communcation ports for battery and WiFi(option)

#### **Product Description**

The E-SUN Hybrid Solar Inverter is a reliable power management solution that efficiently integrates solar energy with traditional grid power. It features pure sine wave output, ensuring stable and clean energy delivery for both on-grid and off-grid applications. With dual AC outputs and support for hybrid operation, it provides flexible energy management to meet diverse energy needs. Built-in MPPT technology maximizes solar energy utilization, while a robust anti-dust kit makes it ideal for harsh environments. Wi-Fi and GPRS compatibility offer remote monitoring and control, adding convenience for users.

Hybrid function

Dual AC output

Built-in anti-dust kit for harsh enviroment

Smart battery charge design to optimize battery life

environments. Wi-Fi and GPRS compatibility offer remote monitoring and control, adding co				
BEST SOLAR PANEL CONFIGUTATION				
Max generated from solar charger	5000W	6000W		
Best Panelconfiguration	540Wp/39V*9pcs (4860Wp) 9S Strings and 1S Parallel	410Wp/39V*14pcs (5740Wp) 7S Strings and 2S Parallel		
PHYSICAL				
Product Dimension	L453mm*W312mm*H120mm			
Net Weight	7.0kg	8.2kg		
Package Dimension	L550mm*W393mm*H196mm			
Gross Weight	8.5kg	9.7kg		
OPERATING ENVIRONMENT		-		
Humidity	5%to95%Relative Humidity(Non-condensing)			
Operation Temperature	0°C-50°C			

TECHNICAL PARAMETER			
Model	E-SUN 4.2KVA	E-SUN6.2KVA	
PF	0.9	0.9	
AC INPUT			
Voltage	230VAC		
SelectableVoltageRange	170-280VAC (UPS Mode),90-280VAC(APP Mode)		
Frequnecy Range	50Hz/60Hz(Auto adaptive)		
ACOUTPUT			
AC Voltage Regulation (Batt Model)	230VAC±5%		
Surge Power	7000VA	11000VA	
Efficiency(Peak)	93.5%	94%	
Transfer Time	Computers(UPS Mode)10ms, Appliance(APP Mode)10ms		
Wave form	Pure sine wave		
BATTERY			
Battery voltage	24.0VDC	48.0VDC	
Floating Charge Voltage(Adjustable)	28.0VDC	56.0VDC	
Constant Charge Voltage(Adjustable)	28.8VDC	57.6VDC	
Overcharge Protection	30.0VDC	60.0VDC	
MPPT SOLAR CHARGER&ACCHARGER			
Maximum PVArray Power	5000W	6000W	
MPPTRange Operaton Vol	40V-450VDC	120V~450VDC	
Maximum PVArray Open Circuit Vol	500VDC	500DC	
Standby Power Consumption	33W	67W	
Maxmum Solar Charge Curren	tMPPT 100A	MPPT 100A	
Maxmum Trace Efficiency	99.5%		
Maxmum AC Charge Current	100A	100A	
Maxmum Charge Current	100A	100A	
A 1' 1'			

# Application

This hybrid inverter is perfect for residential and small commercial solar energy systems that require a stable, reliable power supply. It can be used for homes, small businesses, or backup power solutions. Its capability to run without batteries and flexibility to integrate with the grid make it an ideal choice for areas with intermittent power supply or those looking to reduce electricity costs by utilizing solar power efficiently.

## **Shipping Methods**

Supports global air and sea shipping.



•

willa@fuhaosolar.com



fuhaosolar.com

Rm3810 Baoli E Building Pa Zhou Haizhu district Guangzhou